

# Contributions to the Study of Energy Flow at Supercharger Groups for Marine Engine

Ion Serbanescu

**Abstract**—The paper was developed using data from literature but also my experience in the operation of machines and installations on board as chief engineer. In this paper we defined key functional parameters that define and influence the energy flows of supercharging groups at ships engines which have to ensure safe operation for all operating regimes.

**Keywords**- Marine engine,supercharges, fluid flow, air temperature, ait compressorr

## I. INTRODUCTION

Supercharging unit is freely rotatable; the gas turbines convert the energy flow in mechanical power that is transmitted to a compressor supplying air energy flow necessary for gas exchange in thermal cylinders engine.

## II. DEFINITIONS AND OPERATING PARAMETERS DETERMINATION

### A. Hourly fuel consumption

Functional characteristics of the engine can be presented in table view or graphical representations. With the processing of the specific fuel consumption  $C_e = f(P_e)$ , figure 1 [B2] we obtain the hourly fuel consumption of the engine, which can be verified by direct experimental determination.

$$C_h = C_e \cdot P_e \left[ \frac{Kg Cb}{h} \right] \quad (1)$$

Where:

$C_e \left[ \frac{Kg Cb}{h} \right]$  - actual specific fuel consumption

$P_{e\ cyl} [KW]$  - effective power corresponding to a cylinder

$P_e [KW]$  - actual engine power




Fig. 1: Performance curves for marine engine MAN B&W [B2]

### B. Power flow available

Energy flow obtained by burning the fuel named energy flow available:

$$\dot{Q}_d = \frac{C_h Q_i}{3600} [KW] \quad (2)$$

$C_h \left[ \frac{Kg Cb}{h} \right]$  - hourly fuel consumption

$Q_i \left[ \frac{KJ}{KgCb} \right]$  - lower calorific power of fuel

Manuscript received November 23, 2015.

Ion Serbanescu, Eng. PhD attendee Military Technical Academy, Bucharest, <http://www.mta.ro/>

## Contributions to the Study of Energy Flow at Supercharger Groups for Marine Engine

### C. Actual engine power

Actual engine power is determined by the relation:

$$P_e = \eta_e \cdot \dot{Q}_d [KW] \quad (3)$$

Or else

$$P_e = \eta_e \cdot \frac{c_h Q_i}{3600} [KW] \quad (4)$$

Or else

$$\frac{1}{C_e} = \eta_e \cdot \frac{Q_i}{3600}$$

### D. Specific fuel consumption:

$$C_e = \frac{1}{\eta_e} \cdot \frac{3600}{Q_e} \left[ \frac{Kg \text{ Cb}}{KWh} \right] \quad (5)$$

### E. Effective yield:

$$\eta_e = \frac{1}{C_e} \cdot \frac{1}{Q_i} [-] \quad (6)$$

For reference conditions ISO 3046/2002 from [B2], lower calorific power  $Q_i = 42700 \left[ \frac{KJ}{Kg \text{ Cb}} \right]$

Table 1. Functional features

$P_{ecil}$ [KW]	n [rpm]	$C_e \left[ \frac{Kg \cdot Cb}{KWh} \right]$	$Q_i \left[ \frac{KJ}{Kg \cdot Cb} \right]$	$K_p$	$K_n$
1190	78	0.170	42700	0.5	0.743
1785	95	0.167	42700	0.75	0.91
2380	105	0.170	42700	1	1

Where:

$K_p = \frac{P_{eexp}}{P_{en}}$  - load factor or power ratio

$K_n = \frac{n_{exp}}{n_n}$  - revs report

$P_{eexp}$  - effective operating power

$P_{en}$  - nominal effective power

$n_{exp}$  - operating revs

$n_n$  - nominal revs

## III. FLUID FLOW

### A. Specific air flow

It determines for the conditions:

- a) Burning specific air flow
- b) Gas exchange specific air flow

$$a) d_{ard} = m_{aert} \cdot \alpha_{ard} \cdot C_e \left[ \frac{Kg \text{ air}}{KWh} \right]$$

$$b) d_{asg} = m_{aert} \cdot \alpha_{sg} \cdot C_e \left[ \frac{Kg \text{ air}}{KWh} \right]$$

Where:

$m_{aert} \left[ \frac{Kg \text{ air}}{kg \text{ cb}} \right]$  - theoretical air mass needed to burn 1 Kg of fuel; it's determined according to elemental analysis of the fuel

For liquid fuel:

$$m_{aert} = 13,5 \div 14 \left[ \frac{Kg \text{ air}}{Kg \text{ cb}} \right];$$

$\alpha_{ard} = 1.4 \div 3$  - excess air ratio for burning;

$\alpha_{sg} = 2.2 \div 4.6$  - excess air ratio for gas exchange;

### B. Specific gas flow

$$d_g = d_{asg} + C_e \left[ \frac{Kg \text{ gas}}{KWh} \right] \quad (9)$$


Or else:

$$d_g = (m_{aert} \cdot \alpha_{sg} + 1) \cdot C_e \left[ \frac{Kg \text{ gas}}{KWh} \right] \quad (10)$$

## IV. ENGINE SUPERCHARGING

Engine supercharging is done with supercharging groups consisting of gas turbine an air compressor. From figure 1. [B2] we determine the temperature drop of the gas in the gas turbine.

### A. The fall of temperature turbine



$P_{ecil}$ [KW]	$k_p$	$\Delta \tan TG$ [°C]
1190	0.5	85
1785	0.75	120
2380	1.00	155

$$\Delta \tan TG = tg_1 - tg_2 [°C];$$

**B. Temperature rise in the compressor**

Air temperature increase in the air compressor

$$\Delta t_{aK} = \Delta T_{aK} ; \Delta t_{aK} = t_{ref} - t_0 [^{\circ}C]$$

$$\Delta T_{aK} = T_{ref} - T_0 [K]$$

**C. Boost energy flows on supercharging aggregate**

Supercharger group in free rotation requires energy balance between drive powers of compressor whit the effective power of the gas turbine.

**a) The power required to drive the compressor**

$$P_{antR} = \frac{1}{\eta_k} \cdot \frac{d_{asg} \cdot P_e}{3600} \cdot ca \cdot \Delta t_{aK} [KW] \quad (11)$$

**b) Effective power turbine**

$$P_{eTG} = \eta_{TG} \cdot \frac{d_g \cdot P_e}{3600} \cdot cg \cdot \Delta t_{gTG} [KW] \quad (12)$$

And

$$P_{antK} = P_{eTG} [KW] \quad (13)$$

Ca  $\left[ \frac{KJ}{KG \cdot grd} \right]$  - air specific heat; Cg  $\left[ \frac{KJ}{KG \cdot grd} \right]$  - gas specific heat;

$\eta_k$  - effective yield of the compressor;  $\eta_{TG}$  - effective yield of the gas turbine;

According to the relation (13) we obtain:

$$\frac{1}{\eta_k} \cdot d_{asg} \cdot Ca \cdot \Delta t_{aK} = \eta_{TG} \cdot d_g \cdot Cg \cdot \Delta t_{gTG} \quad (14)$$

And results are:

$$\Delta t_{gTG} = \frac{1}{\eta_k \cdot \eta_{TG}} \cdot \frac{d_{asg}}{d_{gTG}} \cdot \frac{Ca}{Cg} \cdot \Delta t_{aK} [^{\circ}C] \quad (15)$$

And

$$\Delta t_{aK} = \eta_k \cdot \eta_{TG} \cdot \frac{d_{gTG}}{d_{asg}} \cdot \frac{Cg}{Ca} \cdot \Delta t_{gTG} [^{\circ}C] \quad (16)$$

Yield of the supercharging group:

$$\eta_{GSA} = \eta_k \cdot \eta_{eTG} \quad (17)$$

Discharge temperature from the supercharging air compressor:

$$T_{refk} = T_0 \cdot \left( \frac{P_{ref}}{P_0} \right)^{\frac{n_s-1}{n_s}} [K] \quad (18)$$

Where:

$T_0 [K]$  - ambient air temperature

$P_0 [bar]$  - ambient air pressure

$n_s$  - polytropic compression exponent of the air inside the compressor

Relation (15) becomes:

$$\Delta t_{gTG} = \frac{1}{\eta_{GSA}} \left( \frac{m_{air_t} \cdot \alpha_{sg}}{m_{air_t} \cdot \alpha_{sg} + 1} \right) \cdot \left( \frac{Ca}{Cg} \right) \cdot \Delta t_{aK} [^{\circ}C] \quad (19)$$

Relation (16) becomes:

$$\Delta t_{aK} = \eta_{GSA} \cdot \left( \frac{m_{air_t} \cdot \alpha_{sg} + 1}{m_{air_t} \cdot \alpha_{sg}} \right) \cdot \left( \frac{Cg}{Ca} \right) \cdot \Delta t_{gTG} [^{\circ}C] \quad (20)$$

The discharge pressure of the air is determined from Fig 1 [B2]

The yield  $\eta_{GSA}$  is determined from Fig 2 [B1]




Fig. 2: Range of turbocharger efficiency [B1]

Table 2 – Functional characteristics for the supercharging group

$K_p$	$T_0$ [K]	$n_s$	$P_{ref}$ [bar]	$T_{ref}$ [K]	$\Delta t_{aK}$ [ $^{\circ}C$ ]	$\eta_{GSA}$	$\Delta t_{gTG}$ [ $^{\circ}C$ ]
0.5	318	1.35	2.00	381	63	0.62	83
0.75	318	1.35	2.80	415	97	0.65	121
1.00	318	1.35	3.80	449	131	0.68	157

**V. DETERMINATION OF AIR EXCESS**

**A. Mass of fuel injected per cycle**

For the cyclic functioning of the engine is determined

The number of cycles per minute  $N_{cm} = \frac{2n}{\tau} \left( \frac{cycles}{min} \right)$

The number of cycles per second  $N_{cs} = \frac{2n}{\tau} \cdot \frac{1}{60} \left( \frac{cycles}{s} \right)$

The number of cycles per hour  $N_{ch} = \frac{2n}{\tau} \cdot 60 \left( \frac{cycles}{h} \right)$

Where:

$n \left( \frac{rot}{min} \right)$  - RPM of the engine;

$\tau$  - number of races the piston perform for one engine cycle

$\tau = 2$  - for M2T engines – the piston performs 2 races per cycle;

$\tau = 4$  - for M4T engines – the piston performs 4 races per cycle;

$m_c = \left[ \frac{Kg \ cb}{cycle} \right]$  - fuel mass injected per cycle

$$m_c = \frac{c_e \cdot P_{eclt}}{\frac{2n}{\tau} \cdot 60} \left[ \frac{Kg \ cb}{cycle} \right] \quad (21)$$

Table 3 – Fuel mass injected per cycle

$K_p$	$K_p$	$C_e$ $\left[ \frac{kg \ cb}{KWh} \right]$	$n$ $\left[ \frac{rot}{min} \right]$	$\tau$	$m_c$ $\left[ \frac{Kg \ cb}{cycle} \right]$	$L.I = \frac{m_{c \ exp}}{m_{cn}}$
0.5	0.5	0.170	78	2	0.04323	0.660
0.75	0.75	0.167	95	2	0.0523	0.815
1.00	1.00	0.170	105	2	0.0642	1.00

Where:

L . I – load indicator;  $m_{c_{exp}}$  - fuel mass injected into operation;  $m_{c_n}$  - fuel mass injected into nominal conditions

**B. Air mass needed per cycle for burning**

$$m_{air_{cycle}} = m_{air_t} \cdot \alpha_{ard} \cdot m_c \left[ \frac{kg \text{ air}}{cycle} \right] \quad (22)$$

Table 4 – Air mass needed per cycle for burning

$m_a$ [kg air] [cycle]	$m_{aer_t}$ [kg air] [kg cb]	$m_{air_{cycle}} \left[ \frac{kg \text{ air}}{cycle} \right] = f(\alpha)$						
		1.4	1.6	1.8	2	2.2	2.5	2.8
0.0432 3	13.6	0.82 3	0.94 1	1.058	1.1 8	1.2 9	1.47	1.65
0.0523	13.6	0.99 6	1.14	1.28	1.4 2	1.5 6	1.78	1.99
0.0642	13.6	1.22 2	1.39 7	1.571 6	1.7 5	1.9 2	2.18 3	2.44 4

**C. Determination of air excess for the reference engine**

For the reference engine from [B1]

D = 0.6 [m] – cylinder diameter; S = 2.4 [m] –piston stroke

The volume of the piston race is determined by:

$$V_S = \frac{\pi \cdot D^2}{4} \cdot S [m^3]; V_S = 0.6786 [m^3]$$

$\epsilon = 14.45$  – the compression ratio

Combustion chamber volume - the minimum volume of engine fluid

$$V_{CA} = V_{min_f} = \frac{V_S}{\epsilon - 1}; V_{CA} = 0.0504 [m^3]$$

The volume of the piston race affected by the presence of window streak

$$\Psi_{FB} = 0.09 \div 0.12; \Psi_{FB} = \frac{h_{FB}}{S};$$

$h_{FB} [m]$  - the height of window streak

$$V_{FB} = V_S \cdot \Psi_{FB}; V_{FB} = 0.06786 [m^3]$$

At the end of the gas exchange, the covering of the window streak, the air needed for burning is retained in the volume:

$$V_{aer_{cil}} = V_S + V_{CA} - V_{FB} [m^3] \quad (23)$$

$$V_{aer_{cil}} = 0.66114 \left[ \frac{m^3}{cycle} \right]$$

For this volume is calculated the air mass needed for one cycle:

$$m_{aer_{ciclu}} = \frac{P_{aer_{cil}} \cdot V_{aer_{cil}}}{R T_S} \left[ \frac{kg \text{ air}}{cycle} \right] \quad (24)$$

$$R = 0.286 \left[ \frac{KJ}{Kg \text{ grd}} \right]; T_S = 360 [K]$$

Results:

$m_{aer_{ciclu}} = 2.44 \left[ \frac{kg \text{ air}}{cycle} \right]$  for which corresponds the air excess coefficient  $\alpha_{ard} = 2.795$  correspondent to the nominal operating system for which was projected and planed the engine.

**VI. CONCLUSION**

1. Monitoring functional parameters allow correlation with geometric engine parameters for safe operation by preventing thermal and mechanical overloads;

2. Mass and energy flows of the supercharging unit depend on the engine load, ambient parameters but also fuel quality;

3. Using calculation and experimental determinations permit correct interpretation of the functional interactions between the combustion engine and supercharger unit;

4. The reference values of functional parameters can be presented in tabular or graphic, by the designer and manufacturer and must be used for comparison in various situations of exploitation;

5. Correlation boost energy flows on supercharging aggregate can be done by comparing the functional parameters of the flue gas flow.

**REFERENCES**

- (1) Project Guide Exhaust Gas Turbocharger TCA – series Version 6/2007
- (2) MAN B&W S60MC- C8 - project Guide Camshaft Controlled Two Stroke Engines
- (3) Anastase Pruiu - Instalatii energetice navale - Editura Leda & Muntenia Constanta 2000

**Ion Serbanescu**, Eng. PhD attendee at Military Technical Academy of Bucharest. Naval Academy Constanta graduated on 1985. Actually Chief engineer on different Shipping Company’s and different type of ships, whit different type of equipments. International and Romanian scientific various comferinte, active participant whit various articles publicized on different magazine and technical journals.